

POWER SUPPLY UNIT N125/22 640 MA



Similar to image

Technical data:

Design type		voltage supplies
Type, explanations / additionally		integrated reactor, 640 mA, additional output without reactor, 29 V DC
Type of mounting		modular installation device
Number of pitch units for width		4
Bus system / can be used / EIB/KNX		Yes
Bus system / usable / RF bus system		No
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Output current		640
Rated operational voltage, AC		120 to 230
Output voltage, DC	V	29
Number of installation bus lines		1
Number of chokes / integrated		1
Output current / maximum	mA	640
Product component / Buffer battery		No
Product component / LED		Yes

Certificates/approvals:

Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1125-1AB22/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1125-1AB22

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 1, 2013