

DUAL SENSOR AP254/02



Similar to image

Technical data:	
Design type	brightness
Type, explanations	combination indicator surface-mounted 254/02
Design of the sensor	multiple sensor
Bus system / can be used / EIB/KNX	Yes
Bus system / usable / RF bus system	No
Bus system / usable / Powernet bus system	No
Bus system / usable / LON bus system	No
Temperature measuring range	-25 to +55 °C
Type of mounting	surface mounted
Color	white
Protection class IP	IP54
Design of sensor / weather station	No
Suitability for interaction / DCF77	No
Brightness measuring range	1 to 100000 lux
Product component	
• integrated / Bus coupling	Yes
• analog input	No
• Digital input	Yes

• Heating

No

Product function / adjustable acoustic signal

No

#### Certificates/approvals:

General Product  
Approval

Declaration of Conformity



GOST



EG-Konf.

#### Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1254-3EY02/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5WG1254-3EY02](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1254-3EY02)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 1, 2013