

UNIVERSAL DIMMER UP 525/13 1X 250W,
AC 230V WITHOUT MOUNTING FRAME



Similar to image

Technical data:		
Design type		lighting
Type, explanations		Universal Dimmer
Design, description / additional supplementary		as flush-mounted device without mounting frame
Design of the product		dimming actuator
Type of mounting		flush mounted
Number of analog outputs		1
Adjustable real power	W	10 ... 250
Operating voltage		
• rated value	V	230 ... 250
Product component		
• integrated / Bus coupling		Yes
• Extension input		No
• LED		No
Bus system / can be used / EIB/KNX		Yes
Bus system / usable / RF bus system		No
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Product function		

• Parallel operation		No
• direct operation		No
Extension de produit / en option / puissance additionnelle		No
Dimensions width in mm		51
Operating frequency		
• rated value	Hz	60 ... 50
Type of load		universal
Protection class IP		IP20
Design		flush-mounted
Dimmer performance in W		10 to 250
Electrical output protection against overload and short-circuiting		yes
Load type		R,L,C
Integrated bus coupling unit		yes

Certificates/approvals:

Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1525-2AB13/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1525-2AB13

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jul 1, 2013