



## Main

Commercial Status	Commercialised
Range of product	Canalis
Product name	KS
Product or component type	Tap-off unit
[I <sub>e</sub> ] rated operational current	63 A at 35 °C
Fuse type	Diazed - E33 - conforming to DIN
Mounting mode	Plug-in
Tap-off unit polarity	3L+N+PE

## Complementary

Device application	Medium power distribution
[U <sub>e</sub> ] rated operational voltage	230...690 V depending on protective device
[U <sub>imp</sub> ] rated impulse withstand voltage	6.8 kV
[U <sub>i</sub> ] rated insulation voltage	690 V depending on protective device 500 V depending on protective device 400 V depending on protective device
Network frequency	50/60 Hz
Protection type	Fuse
Electrical connection	Cable clamp terminal ISO63 25 mm <sup>2</sup> rigid Cable clamp terminal ISO63 25 mm <sup>2</sup> flexible
Tap-off unit disconnection mode	By opening the door
Tap-off unit connector type	With fixed polarity
Door opening side	Right
Door opening size	545.5 mm
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Provided equipment	Fuse not supplied
Standards	IEC 60439-2 IEC 61439-6
Colour	RAL 9001 white
Width	44 mm
Depth	128 mm
Height	202 mm
Product weight	2.4 kg

## Environment

Earthing system	IT - tap-off unit IT - busbar trunking TN-S - tap-off unit TT - tap-off unit TN-C - busbar trunking TN-S - busbar trunking TT - busbar trunking
-----------------	---

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1012 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations