

Busch-triton® control elements
Control element, 5/10gang, with IR interface and RTC
Busch-triton®



With integrated KNX bus coupler.

With labelling field.

Rocker switch left/right (switching/dimming/blind/value sender/light scenes/fan function).

Master/slave configuration.

With base-load operation.

Control element with room thermostat function for triggering the heating, ventilation and fan-coil actuators.

The controller is a constant room temperature controller for ventilator convectors (fan coils) in 2-pipe and 4-pipe systems and conventional heating or cooling systems.

The fan stage can be switched manually or in automatic mode.

To control up to 13 IR channels (RC5) using Busch-Remote control IR mobile remote control 6010-25 or 6020-.../6021... .

Klasse des Temperaturreglers 1

Beitrag zur Raumheizungsenergieeffizienz 1,0%.

Control element: rocker switch left/right, Display elements: Two LED per rocker via separate communication object for status (Red/ Green/ OFF) or orientation light.,

Connections: , KNX-line: Bus connection terminal

Protection class (Device): IP 20, Temperature range (Device): -5 °C to 45 °C,

Dimensions: (L x W x D): 159 mm x 90 mm,

As required, you can find the programmable functions in the current application description, which you can download in the Support Centre on our Internet page., For compatible lettering software, visit www.BUSCH-JAEGER-labelingtool.com.

Order Code : 6320-0-0070

Article No. : 6321/58-260-500

EAN: 4011395201527